

LRHD250RII

Top Discharge Series

Cooling / Heating	Cooling & Heating
Compressor Control	Non-Inverter
Compressor HP	25 HP
Cooling Capacity	62.5 kW (213,200 BTU/h)
Heating Capacity	62.5 kW (213,200 BTU/h)
Recommended Water Volume	18750 L @30°C ambient / 20°C target
Min. Set-point	6°C (43°F)
Target Water Temp. Range	6°C~35°C (43°F~95°F)
Voltage	380V 50Hz
Max Current	60 A
Refrigerant	R410a
Heat Exchanger	Titanium Tube
Expansion Valve	EEV (Electronic Expansion Valve)
Water Connection	Ø75 flange
Min. Water Flow	25 m³/h
Noise Level	65 dB(A)
Dimensions (W×D×H)	1882×731×2019 mm
Net Weight	476 kg
Control Panel	Water-resistant
APP / WiFi Control	Yes
Warranty	1 Year

Recommended water volume is calculated at 30°C ambient / 20°C target water temperature, continuous operation, with standard insulation. Performance data are reference values; full specifications are subject to the manufacturer's product catalogue. Standard mass-production configuration; market-specific voltage, water-connection fittings, and refrigerant type are available on request. Specifications are subject to change without notice. Confirm the latest parameters with your sales contact before ordering. Net weight is approximate.

Web: kool-blaster.com Inquiry: info@kool-blaster.com Support: support@kool-blaster.com